

# ML-7

## Monitor / Monitor

### Product description

The ML-7 monitors are LCD monitor specifically designed for video surveillance applications where a small monitor is required. They are suitable for mounting on bracket or flush mounting and are ideal for installation on vehicles.

### Package Contents

- Monitor base bracket and built-AV cable for connection
- IR remote control
- 

### Connections

The monitor is provided with a connecting cable to connect to the connector that protrudes from the monitor itself. At the other end of the cable connects the 12VDC power supply (to the black cable connects the negative and the red positive).

The monitor is suitable for analog cameras. At the yellow connector connects the first video input to the white second video input.



### panels

1. jack (optional - not usable in this template)
2. Operating status LEDs
3. Video Switch 1/2 video (V1 / V2)
4. MIRROR function (horizontal / vertical)
5. Menu
6. Volume - (minus key)

7. Volume + (plus key)
8. Power button
9. Remote sensor
10. TFT / LCD Screen

### Using the Monitor

Press the power button to turn on the monitor. Press AV1 / AV2 to display the video input 1 or 2.

Press

MENU button to enter the

programming.

### Access the menu

Press the MENU button to access the programming menu. The set language

factory

English. And 'possible to select the Italian language by pressing 6 times the menu button and choosing ITALIAN with the +/- keys.

Use these buttons:

MENU: it allows access to the menu and browse programming sections +/- BUTTONS: To vary a parameter In the programming menu it is possible to set the BRIGHTNESS, the CONTRAST, SATURATION, the MODE (16: 9 or 4: 3) the ROTATE (FEATURE ROLLOVER IMAGE / MIRROR), the LANGUAGE and reset the factory settings in the RESET using the +/- buttons

### Flush mounting

The first thing to do is to remove the monitor from FIXING BASE pressing

the two

buttons present on the base and extracting the latter from the monitor. Once removed the monitor from its base must provide to fasten it with screws or dowels

in

output cable correspondence. Then

connect and

reinsert the monitor in the fixing base.

### Bracket

The special jointed bracket of ML-7 monitor allows mounting on any surface without the need for additional accessories. Take the monitor from the base recessed and fasten the bracket to the rear sled.

### Technical data

